




LEGEND 6000 XGBK
Cod. **02060208** EAN **8422248102544**



- Touch Control Panel** with automatic shut-down timer and cleaning filters indicator
- 9 extraction levels
- Extraction power (according to UNE/EN 61591): **530m³/h** - 190m³/h
- Sound power (Reg.(EU) n°65/2014): 42dB(A)**, maximum: 59dB(A)
- BRUSHLESS motor. Ultra silent. Maximum energy consumption **70W**
- High efficiency Strip Led lighting**
- Easy-to-install system
- MAX panelled stainless steel filters dishwasher washable
- Stainless steel finishing and black glass
- Max. Pressure: 220 Pa
- 150 mm outlet diameter
- Energy Class: A++**

► **Accessories (not included)**

Active charcoal filterCod. 02859492 / EAN 8422248097697.....



Code	02060208
EAN	8422248102544
Model	LEGEND 6000 XGBK
Type	Box
Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564	
AEC (Annual Energy consumption) (kWh/annum)	12,96
EEL class (Energy Efficiency Class)	A++
FDE (Fluid Dynamic Efficiency)	31,7
FDE class (Fluid Dynamic Efficiency Class)	A
LE (Lighting Efficiency) (lux/W)	37
LE class (Lighting Efficiency Class)	A
GFE (Grease Filtering Efficiency)	81,7
GFE Class (Grease Filtering Efficiency class)	C
Air flow at minimum speed (m3/h)	188,74
Air flow at maximum speed (m3/h)	529,19
Air flow at intensive speed (TURBO) (m3/h)	-
Sound Power Level at minimum speed (dB)	42,08
Sound Power Level at maximum speed (dB)	59
Sound Power Level at intensive speed (TURBO) (dB)	-
Po (Power Consumption in off mode) (W)	0,45
Ps (Power Consumption in standby) (W)	-
Integration directive EU 66/2014	
f (Time Increase Factor)	0,859
EEL (Energy Efficiency Index)	35,43
QBEP (Flow Rate at Best Efficiency Point) (m3/h)	222,03
PBEP (Static Pressure Difference at Best Efficiency Point) (Pa)	188,65
WBEP (Electric Power Input at Best Efficiency Point) (W)	36,7
WL (Nominal Power Consumption of Lighting system) (W)	2
EMIDDLE (Average Illumination of Lighting system on Cooking surface) (lux)	74
External Dimensions	
Width (mm)	595
Depth (mm)	500
Total max height(mm)	998
Total min height(mm)	548
Outlet Diameter (mm)	150
Characteristics	
Motor	BLDC600
Extraction Levels	9
Motor Maximum Power Consumption	70
Maximum Pressure	220
Intensive Speed (TURBO) Pressure	-
Control Type	T02
Automatic shut-down timer	√
Electronic Filter Saturation Indicator	√
Filter Type	Metallic
Anti-grease Filter Number	2
Inner Shield	-
Lighting	
Light Type	CSLED
Adjustable Intensity Lighting	
N° of Lamps	1
Installation	
Minimum height distance to a electric worktop hob (mm)	650
Minimum height distance to a gas worktop hob (mm)	650
Installation with Outlet tube to the exterior / Recirculating	BOTH
Easy Installation System	√
Electric Connection	
Total Rush Power (W)	72
Rated Voltage (V)	220-240
Network Frequency (Hz)	50-60
Electrical Insulation Class	CLASS I
Plug	√
Accessories	
Upper Decorative tube Extension	
White Decorative Tube	-
Black Decorative Tube	-
Island Tube Enhancer	-
Check Valve	-
MAX PRO Metal Filter	-
Metal Filter	02800975
DUAL Filter (metal + active charcoal)	-
Active Charcoal Filter	02859492
Noiseless Flexible Duct	02893002